

Datasheet Breathing filter 39 ASt

Designation: Respiratory protection insert filter A1-P2 R D
Combination filter to DIN EN 14387 - filter type/class
A1 - P2 R D as part of a respiratory protective device
to DIN EN 133 - filter device

Description: Cylindrical housing with profiled perforated base and lid

Article-Number: 924000 (5 pieces in folding box)

Application: In conjunction with filter holder 5570/70 on breathing connection - full face masks (DIN EN 136) or half masks (DIN EN 140) with round thread connection - for protection against organic gases and vapors with a boiling point above 65°C and against harmful particles
R = Reusable - reusable against particles
D = particularly resistant to clogging by dust
(storage test with dolomite dust according to EN 143)

Standards: DIN EN 133 Respiratory protective devices - Classification
DIN EN 148-1 Respiratory protective devices - Threads for breathing connections - Round thread connection
DIN EN 14387 Respiratory protective devices - Gas filters and combination filters

Identification colors: brown - white (adhesive label)

Materials: Housing, perforated disk Aluminum alloy
Filter medium Activated carbon
Non-woven discs Polypropylene
Sealing foil Polypropylene

Dimensions: Diameter approx. 87 / 90 / 95 mm
Height approx. 50 mm

Weight: approx. 120 grams

Inhalation resistance: < 1.7 mbar at 30 l/min constant air flow
< 6.4 mbar at 95 l/min constant air flow

Filter flow rate: sodium chloride test at 95 l/min: < 6 %
Kerosene oil test at 95 l/min: < 6 %

Storability: 6 years - from date of manufacture (protected from cold, heat and moisture)

Handling: Only remove the filter from the packaging immediately before use and insert into the filter holder 5570/70.
Screw the filter holder firmly into the connection piece of the mask.
If necessary, place pre-filter 35/70 in the pre-chamber of the cover.

Revision 07.2026 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de
Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt



Datasheet Breathing filter 39 ASt

Main applications:	Spraying solvents (boiling point >65°C) aerosols, herbicides and pesticides (non-toxic), rock dust, glass wool, mineral fibers, wood dust, soot, steel dust, bacteria and viruses.	
Service life:	The service life of combination filters depends on several factors such as the concentration of harmful gases, ambient temperature, humidity, work intensity, posture, etc. and therefore cannot be determined in advance. Opened filters must be replaced after 6 months at the latest.	
Application limits:	according to technical rules for hazardous substances TRGS 900 "Occupational exposure limits"	
	with half/quarter mask (particle filter):	10 times the occupational exposure limit value
	with full face mask (particle filter):	15 times the occupational exposure limit value
	with half/quarter mask (gas filter):	30 times the occupational exposure limit value
	with full face mask (gas filter):	400 times the occupational exposure limit value
	Maximum permissible	
	Gas concentration:	of gas filter class 1 (A1, B1, E1, K1) = 1,000 ml/m³
Instructions for use:	The use of breathing filters requires a basic knowledge of the function and and handling of respiratory protective devices. Information on this can be found in the trade association regulations and rules, in particular in DGUV Rule 112-190. The use of respiratory protective devices generally means additional strain for the person wearing the respiratory protective device. Most respiratory protective devices require occupational health screening in accordance with the "Ordinance on Occupational Health Care" (ArbMedVV). Damaged filters must not be used.	
Regulations / rules:	Regulation (EU) 2016/425 on personal protective equipment PPE Usage Ordinance (PSA-BV) Ordinance on occupational health care (ArbMedVV) BGV A1 Employer's Liability Insurance Association Regulation for Safety and Health at Work - Accident Prevention Regulation - Principles of Prevention DGUV Rule 112-190 Employer's liability insurance association rules for safety and health at work - "Use of respiratory protective equipment" Hazardous Substances Ordinance (GefStoffV) with associated Technical Rules for Hazardous Substances (TRGS), in particular TRGS 402 "Determination and assessment of hazards during activities involving hazardous substances: Inhalative exposure" and other technical rules for hazardous substances.	

Revision 07.2026 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de
Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt

Datasheet Breathing filter 39 ASt

Order details:	Article number	Description
	924000	Combination filter 39 ASt
	111200	Full face mask BRK 820
	111201	Full face mask BRK 820 V
	111208	Full face mask BRK 820 G
	111400	Full face mask TR 2002 CL3
	202952	Half Mask BariMask HF Rubber
	202953	Half Mask BariMask HF Silicon
	929105	Coarse dust pre-filter 35/70
	929006	Filter holder 5570/70
	111704	Wall container for full face mask including one filter
	111705	Wall container for two full face masks including two filters
	111703	Carrying box B78 for one full face mask and one filter

Revision 07.2026 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de

Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt