

Datasheet Cylinder trolley Air2go LIGHT

Designation: Cylinder trolley Air2go LIGHT

Description: Mobile breathing air supply
For holding two 50 l/300 bar breathing air cylinders,
Mounting device for AirBox with DM1900 for
connection of compressed air hose devices
» Made of stainless steel
» Electrostatic discharge capability
» Hose holder for transporting hoses

Article-Number: 202869

Materials: Chassis made of stainless steel

Dimensions: Height: approx. 156 cm
Width: approx. 72 cm
Depth: approx. 80 cm

Weight: without bottles approx. 56 kg
Maximum total weight: 250 kg

Front wheels: Ø 40 cm, Elastofom wheels

Swivel castors: Ø16 cm with total lock,
Adjustable brake system

Optional equipment

Breathing air storage: 2x50l compressed gas cylinder 300bar
Breathing air supply: up to 28,000 liters
Calculated air supply when using a compressed air hose device with
regulator
Low ventilation: 50 l/min = approx. 560 min;
High ventilation: 100 l/min = approx. 280 min

Breathing air hose: DZS 9 (maximum length 50m each)
Hose holder for transportation

AirBox: Airbox is designed for rough applications and is used to hold and protect
the DM 1900 pressure reducer.



Revision 05.2024 – Errors and omissions excepted. All data are non-binding guide values.

BartelsRieger Atemschutztechnik GmbH

Richard-Byrd-Straße 23 | 50829 Cologne | Phone +49 (0)221 59777-0 | mail@bartels-rieger.de | www.bartels-rieger.de

Ust.-IdNr. DE 815603312 | St.-Nr. 217/5811/1510 | Reg.-Gericht Köln | HRB 54098 | Managing Director: Tobias Rutt