Datasheet Basic Equipment Filter Device



With Safety.

Designation: Basic Equipment Filter Device; with Belt

Description: Corrugated hose with round-thread connectors according to DIN EN

148-1 for attachment to the breathing connection and for accommodating a screw filter with a round-thread connection according to DIN EN 148-1. Equipped with a plastic waist belt and

strain relief.

Article-Number: 934010

Application: Used as an accessory in combination with breathing connections - full-

face masks (DIN EN 136) or half masks (DIN EN 140) with a roundthread connection. It is intended for use when the filter is too heavy for the breathing connection (maximum 300 g for half masks, maximum

500 g for full-face masks), when the filter interferes with the breathing connection during use, or when the pollutant concentration can be brought within the permissible range by relocating the filter. The device transfers the weight to the hip. The carrying

position is adjustable to front, side, or back.

Respiratory protective devices - Full-face masks -Standards: **DIN EN 136**

Requirements, testing, marking

Respiratory protective devices - Half masks and **DIN EN 140**

quarter masks - Requirements, testing, marking

Moplen EP340M, black

Moplen EP340M, black

Polyamide 6 with 30% glass fiber

Chrome-nickel steel

Polypropylene

Corrugated hose 800 mm, connector Ø 22 mm Materials: Anti-static rubber, black Rigid polyethylene

Female threaded connector

Nozzle for round-thread connection Round-thread connector (male thread)

Single-ear clamp

Waist belt Heavy-duty buckle

Waist belt 40 mm × 1400 mm

Corrugated hose with connectors approx. 900 mm × Ø approx. 31 mm

Weight: approx. 300 g

Dimensions:

Order Information: Article- Number Description

> 934010 Basic Equipment Filter Device; with Belt

202952 Half Mask BariMask HF 111200 Full-Face Mask BRK 820 Full-Face Mask BRK 820 V 111201 111208 Full-Face Mask BRK 820 G 111400 Full-Face Mask TR 2002 CL3

Revision 08.2025 – Errors and omissions excepted. All data are non-binding guide values.